Diving Board Resurface Kit MSDS, Super Convoy Base Part One MATERIAL SAFETY DATA SHEET FOR COATINGS, RESINS AND RELATED MATERIALS

DATE OF PREPARATION - 30, 03,2014

MANUFACTURER'S NAME : Kelley Technical Coatings : 1445 South 15th Street ADDRESS

: PO Box 3726 ADDRESS

ADDRESS

: Louisville, Kentucky, 40201-3726 CITY, STATE

EMERGENCY TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (800) 424-9300-INFORMATION TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (502) 418-5086-

SECTION I -- PRODUCT IDENTIFICATION

MANUFACTURER'S CODE IDENTIFICATION :373B

PRODUCT CLASS : Epoxy Base
TRADE NAME : SUPER CONVOY, TURQUOISE BASE

HMIS INFORMATION: HEALTH: 02

FLAMMABILITY : 02 REACTIVITY : 01

PERSONAL PROTECTIVE EQUIPMENT : REFER TO "SECTION VIII"

SECTION II -- HAZARDOUS INGREDIENTS

---- INGREDIENT ---- %BY ACGIH OSHA SAR NUIS MATERIAL DESCRIPTION Cas WEIGHT T.L.V. P.E.L 313 PGMT MATERIAL DESCRIPTION Cas

AROMATIC NAPHTHA

64742-95-6 12.942 100PPM 100PPM N 2-Butoxyethanol

111-76-2 3.0586 25PPM 50PPM N

If indicated above: this material could constitute a personnel hazard.

If the CAS# field above starts with ## then this material is considered a trade secret.

SECTION III -- PHYSICAL DATA

.-----LOWER EXPLOSION LEVEL

1.0 - 1.2 BOILING RANGE HIGH 343 DF LOW 306 DF

3.00 MMHG @ 68DF VAPOR PRESSURE VAPOR DENSITY HEAVIER THAN AIR

EVAPORATION RATE SLOWER THAN BUTYL ACETATE

WEIGHT PER GALLON 14.73 % VOLATILE BY VOLUME 34.79

> MATERIAL SAFETY DATA SHEET PAGE #2

MANUFACTURER'S CODE 373B DATE OF PREPARATION - 30, 03,2014 SUPER CONVOY, TURQUOISE BASE, TRADE NAME

16.91 % VOLATILE BY WEIGHT

% VOLATILE BY WEIGHT 16.91

VOC --- LBS/GAL 2.55 LBS/GAL NO Water 2.55

GRAMS/LITER 306.17 GRAMS/LITER 306.17

SECTION IV -- FIRE AND EXPLOSION DATA

FLAMMABILITY CLASSIFICATION OSHA - CLASS II Page 1

```
Diving Board Resurface Kit MSDS, Super Convoy Base Part One
DOT - COMBUSTIBLE LIQUID UN 1263
LOWEST FLASH POINT T.C.C. 110
LOWER EXPLOSION LEVEL (LEL) 1%
Extinguishing Media: (Yes) - Foam (No) - Alchohol Foam (Yes) - CO2
(Yes) - Dry Chemical (Yes) - Water Fog
Unusual Fire and Explosion Hazards: - Flammable vapors may form explosive
                                                                                     mixtures with air.
Special Fire Fighting Procedures: - Avoid solid stream of water, use fog
                                                            for cooling.
                             SECTION V -- HEALTH HAZARD DATA
To the best of our knowledge, this product does not contain any carcinogenic ingredients.

Effects of Overexposure: - Liquid may cause eye burns. Prolonged skin contact with liquid may cause irritation. Eye, nose and throat irritation may result from exposure to vapor. Narcotic effects occur
       at higher concentrations of vapor.
Primary Route(s) of Entry:
                                        (x) - Dermal
                                                             (X) - Inhalation (X) - Ingestion
Emergency and First Aid Procedures:

    Eye contact: Irrigate immediately and thoroughly with water at least 15 minutes and get medical attention.
    Skin contact: Flush immediately and thoroughly with water.
    Inhalation: Remove from exposure, treat symptomatically and get

       medical attention.
Medical Conditions Prone to Aggravation by Exposure:
              Pre-existing Respiratory, Eye and Skin Conditions.
                                      MATERIAL SAFETY DATA SHEET
MANUFACTURER'S CODE 373B
                                                                       DATE OF PREPARATION - 30, 03,2014
TRADE NAME
                            SUPER CONVOY, TURQUOISE BASE,
                                SECTION VI -- REACTIVITY DATA
Stability: () - Unstable (X) - Stable
Hazardous Polymerization: () - May Occur (X) - Will Not Occur
Hazardous Decomposition Products: - As with any other organic material,
combustion will produce corbon dioxide and probably carbon monoxide.
Conditions to Avoid: - Not applicable.
Incompatibility (Materials to Avoid): - Oxidizing materials can cause a
                                                           vigorous reaction.
______
                      SECTION VII -- SPILL OR LEAK PROCEDURES
Steps to be Taken in Case Material is Leaked or Spilled:
- Eliminate all ignition sources. Flush spill away with water spray.
- Small spills may be collected with absorbant material.
Waste Disposal Method:
    - Mix with a compatible chemical which is less combustible and
    - Observe all federal, state, and local laws concerning health and
 SECTION VIII -- SAFE HANDLING AND USE INFORMATION
Respiratory Protection: - A NIOSH approved respirator for organic vapors
       should be worn if needed.
Ventilation: - Local exhaust recommended.
                          - Mechanical (General) recommended.
                          - Special: None known.
```

Diving Board Resurface Kit MSDS, Super Convoy Base Part One Protective Gloves: - Should be worn.

Eye Protection: - Safety glasses should be worn in any type of industrial operation.

Other Protective Equipment: - Safety shower and eye bath in work area.

Hygienic Practices: - Remove paint from skin contact after exposure.

SECTION IX -- SPECIAL PRECAUTIONS

\_\_\_\_\_\_

## MATERIAL SAFETY DATA SHEET

PAGE #4

MANUFACTURER'S CODE 373B DATE OF PREPARATION - 30, 03,2014 TRADE NAME SUPER CONVOY, TURQUOISE BASE,

Precautions to be Taken in Handling and Storing: Keep away from heat, sparks and open flame.
Keep container closed. Avoid eye contact, prolonged skin contact, and inhalation of high concentrations of vapor. Use with ventilation adequate to maintain vapor concentrations below the TLV of 50 PPM.

Other Precautions: - Hazardous product residue may remain after the product has been removed from its container. Do not reuse "empty" container without commercial cleaning or reconditioning. See also 29 code of federal regulation 1910.1000.