

Filter Media - FOB North Vancouver

Item No	Description	1-11	12-29	30+
11 06 01	#20 Filter Sand (50 Lbs)	\$15.46	\$13.89	\$12.96
11 06 02	#12 Coarse Aquarium Sand (50 Lbs)	\$33.76	\$30.33	\$28.10

NOTE: If you are unsure of the amount of media for your filter, call with the model number and diameter and we will check the specs for you.



DE, Diatomaceous Earth Filter Media

Item No	Size	Per Unit	10+	Pallet Lot of 39
13 07 55	50 LB	\$60.79	\$54.60 @	\$1,407.93

Perlite Filter Media

Item No	Size	Per Unit	10+	Pallet Lot of 39
13 07 50	25 LB	\$67.75	\$60.85 @	\$2,215.60

DE/Perlite Filter Tips

- Good precoat are essential to getting flow, clarity and keeping elements clean.
- Normal doseage is 2 ounces of DE per square foot of filter area, or follow manufacturers precoat dosage instruction.
- Object is to deposit at least 1/16" over all parts of filter elements.
- Precoat flow rate should be no more than 1 US gallon per square foot of filter area.
- Maximum filter flow rate should be no more than 2 USGPM per square foot, and preferably in the range of 1 to 1.5 USPGM per square foot.
- Check filter elements for spots not covered by precoat. This normally indicates body oils of grease or mineral staining on the elements which should be cleaned off or it will affect flow and length of filter cycles.
- Check regularly for warped or broken filter elements and repair as required to maintain filter performance and prevent filter media from leaking into pool.