

## STENNER PERISTALTIC PUMPS

Stenner pumps are the type that use a tube squeezed by a rotating roller to provide the pumping and valving action. The Stenner peristaltic pump is particularly good at high suction lifts where the solution contains solids. This could cure your loss of prime problems. The one thing that should be done is the pump tube should be replaced every six months, having one break and leak bleach everywhere could be a problem if replacement is not done regularly. All pumps shown use 3/8 OD tubing.

Model No	GPD	PSI	Tube #	Price
<b>Fixed Rate Models</b>				
STFP-45MHP3/8#2	10	100	2	\$607.88
STFP-45MHP3/8	22	100	7	\$607.88
STFP-85MHP3/8	40	100	7	\$607.88
STP-85MP/3	85	25	5	\$582.85

### Replacement Pump Tube

UCCP202	2	\$26.35
UCCP205	5	\$32.75
UCCP207	7	\$32.75

### Replacement Pump Head - Quick Pro - New Style

QP107-1	Head, state tube size	\$215.35
---------	-----------------------	----------

### 3/8 Injector Check Valve

UC1NJ3/8	Injector, 3/8 OD Tubing	\$43.75
----------	-------------------------	---------

### 3/8 Suction Line Strainer

ST138	Strainer, 3/8 OD Tubing	\$49.35
-------	-------------------------	---------

### 3/8 Connecting nut with Adapter

UCADPTR	Tubing connector, 3/8 OD Tubing	\$16.35
---------	---------------------------------	---------

### Connecting Nut

MANUT00	3/8 Connecting Nut, 3/8 OD Tubing	\$6.95
---------	-----------------------------------	--------



UCADPTR  
TUBING CONNECTOR  
WITH NUT



MANUT00  
CONNECTING NUT

## Double Walled Containment Tanks

These are polyethylene chemical storage tanks that are sold as tightly fitted nesting pairs to be space efficient. All come with a large quarter turn cap, a flat spot for pump mounting, and a port for a pump suction line. The only color available is light blue, and poly tanks are 100% recyclable. **FOB North Vancouver.**

Item No	Dimensions (Dia X Ht)	Capacity/USG Inner/Outer	Weight Pounds	Price
G120	32" X 47"	120/142	71	\$1885.00
G220	48" X 47"	220/278	132	\$2585.00
G300	48" X 60"	300/375	162	\$3195.00
G500	60" X 61"	500/650	326	\$4185.00



DOUBLE WALLED CONTAINMENT TANKS

## LMI 50 US Gal. Solution Tank C/W Cover

This is a polyethylene Tank suitable for Bleach, Acid or Soda Ash. It comes with a fitting cover that has flat spots for mounting a pump, agitator and liquid level switch. Dimensions are 19" in diameter at the bottom, 22" in diameter at the top, and 40" high. If secondary containment is required please look at page 31, tank model OT 45, which works perfectly and is the same price.

Model No	Description	Price
26350-1	Solution Tank with Cover - 50 usg	\$265.00





### Polyethylene Tanks for Chemical Storage

All the closed top tanks listed below are cylindrical, with integral tops. All the tops have a screw on fill port, the cover/hole size is listed. Tanks can be ordered with a bulkhead fitting at the bottom, but it must be requested with order. Plumbing parts, for instance nipples and valves are not supplied unless ordered separately. Bulkhead fitting sizes vary with the size of the tanks. All the closed top tanks can also be used as secondary containment vessels by cutting off the tops, which can be easily done with a carpenter's handsaw or power tools.

#### Closed Top Tanks

Model No	Capacity	Dimensions	Price
41868	25 usg	18"D x 29"H & 5" lid	\$195.00
41866	50 usg	18"D x 52"H & 5" lid	\$271.08
41862	100 usg	28"D x 42"H & 8" lid	\$446.25
40804	105 usg	23"D x 63"H & 8" lid	\$482.15
VW110	110 usg	29"D x 50"H & 16" lid	\$572.75
41857	200 usg	30"D x 71"H & 8" lid	\$695.00
VW250	250 usg	46"D x 44"H & 16" lid	\$819.25
40215	300 usg	36"D x 79"H & 16" lid	\$789.55
40303	305 usg	49"D x 49"H & 16" lid	\$717.75
VW400	400 usg	46"D x 68"H & 16" lid	\$1109.25
40149	500 usg	48"D x 48"H & 16" lid	\$1022.25



#### Open Top Tanks complete with lids

OT45	45 USG	24"D X 36"H <b>no lid</b>	\$384.25
Otl45	55 USG	27"D X 31"H c/w lid	\$384.25
Otl85	102 USG	29"D X 49"H c/w lid	\$578.55
TT200	240 USG	45"D X 50"H c/w lid	\$799.55
TT400	480 USG	58"D X 54"H c/w lid	\$1193.65

### Clamp Mount Agitators

Motor is 1/3 hp, 110/230V, TEFC. Coupling is stainless steel with 4 set screws. The shaft is stainless steel 5/8" dia. x 48" long. The propellers are stainless steel 4" with three blades. Clamp and motor mount is cast iron. 1750 rpm. Direct drive. Not suitable for D.E.

12 12 51	Clamp mount agitator	\$1046.25
12 12 52	For tanks over 100 gallons, add 1 extra propeller to clamp mount unit (above)	\$187.50
12 12 53	Replacement shaft, 4' X 5/8" OD	\$187.50
12 12 54	Replacement coupling, 5/8" X 5/8"	\$187.50
12 12 55	Replacement prop 4" dia X 5/8" ID	\$187.50
12 12 60	Gear drive mixer	\$POR

Motor is 1/4 Hp T.E. 115V. Gear drive output is 350 rpm. Shaft is 5/8 dia. x 48" long. Propellor is cast 316 SS, approx. 10" in diameter. Suitable for D.E.

