## Zeron Bikini Blue MSDS MATERIAL SAFETY DATA SHEET

FOR COATINGS, RESINS AND RELATED MATERIALS DATE OF PREPARATION - 30,03,2014

MANUFACTURER'S NAME : Kelley Technical Coatings : 1445 South 15th Street **ADDRESS** 

: PO Box 3726 ADDRESS

ADDRESS

: Louisville, Kentucky, 40201-3726 CITY, STATE

EMERGENCY TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (800) 424-9300-INFORMATION TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (502) 363-9721-

SECTION I -- PRODUCT IDENTIFICATION

MANUFACTURER'S CODE IDENTIFICATION :392

PRODUCT CLASS : Epoxy Paint TRADE NAME : Zeron, Bikini Blue, 2pk HMIS INFORMATION : HEALTH : 02 FLAMMABILITY : 02

REACTIVITY : 01

PERSONAL PROTECTIVE EQUIPMENT : REFER TO "SECTION VIII"

-----SECTION II -- HAZARDOUS INGREDIENTS

INGREDIENT MATERIAL DESCRIPTION	Cas	%BY WEIGHT	ACGIH T.L.V.	OSHA P.E.L	_	NUIS PGMT
AROMATIC NAPHTHA	64742-95-6	4.11	100ррм	100ррм	V	N
2-BUTOXYETHANOL BUTOXY PROPANOL	04742-33-0	4.11	TOOPPM	TOOPPM	•	IN
	111-76-2	2.117	25РРМ	50РРМ	Υ	N
	1569-01-3	1.075	Not Estab.	Not Estab.	Υ	N

If indicated above; this material could constitute a personnel hazard.

If the CAS# field above starts with ## then this material is considered a trade secret.

SECTION III -- PHYSICAL DATA

LOWER EXPLOSION LEVEL 1.0 - 1.2

BOILING RANGE HIGH 343 DF LOW 306 DF

VAPOR PRESSURE 3.00 MMHG @ 68DF VAPOR DENSITY HEAVIER THAN AIR

EVAPORATION RATE SLOWER THAN BUTYL ACETATE

WEIGHT PER GALLON 10.23 % VOLATILE BY VOLUME 24.31 % VOLATILE BY WEIGHT 14.72

LBS/GAL No Water 1.65 VOC --- LBS/GAL 1.65 GRAMS/LITER 197.48 GRAMS/LITER 197.48

MATERIAL SAFETY DATA SHEET

DATE OF PREPARATION - 30,03,2014

PAGE #2

PAGE #1

MANUFACTURER'S CODE 392 Zeron, Bikini Blue, 2pk, TRADE NAME

SECTION IV -- FIRE AND EXPLOSION DATA

\_\_\_\_\_\_

## Zeron Bikini Blue MSDS

```
FLAMMABILITY CLASSIFICATION OSHA - CLASS II
DOT - COMBUSTIBLE LIQUID UN 1263
LOWEST FLASH POINT T.C.C. 110 DF
mixtures with air.
Special Fire Fighting Procedures: - Avoid solid stream of water, use fog
                                                                for cooling.
                           SECTION V -- HEALTH HAZARD DATA
To the best of our knowledge, this product does not contain any carcinogenic ingredients.
Effects of Overexposure: - Liquid may cause eye burns. Prolonged skin
       contact with liguid may cause irritation. Eye, nose and throat irritation may result from exposure to vapor. Narcotic effects occur
       at higher concentrations of vapor.
Primary Route(s) of Entry: (X) - Dermal (X) - Inhalation (X) - Ingest Emergency and First Aid Procedures:
- Eye contact: Irrigate immediately and thoroughly with water at least 15 minutes and get medical attention.
- Skin contact: Flush immediately and thoroughly with water.
- Inhalation: Remove from exposure, treat symptomatically and get
                                                          (X) - Inhalation (X) - Ingestion
      medical attention.
Medical Conditions Prone to Aggravation by Exposure:
      - Pre-existing Respiratory, Eye and Skin Conditions.
                         SECTION VI -- REACTIVITY DATA
Stability: () - Unstable (X) - Stable
Hazardous Polymerization: () - May Occur (X) - Will Not Occur
Hazardous Decomposition Products: - As with any other organic material,
combustion will produce corbon dioxide and probably carbon monoxide.
Conditions to Avoid: - Not applicable.
Incompatibility (Materials to Avoid): - Oxidizing materials can cause a
                                                                             vigorous reaction.
                                    MATERIAL SAFETY DATA SHEET
                                                                                           PAGE #3
MANUFACTURER'S CODE 392
                                                                   DATE OF PREPARATION - 30,03,2014
TRADE NAME
                         Zeron, Bikini Blue, 2pk,
                         SECTION VII -- SPILL OR LEAK PROCEDURES
Steps to be Taken in Case Material is Leaked or Spilled:
- Eliminate all ignition sources. Flush spill away with water spray.
- Small spills may be collected with absorbant material.
Waste Disposal Method:
    - Mix with a compatible chemical which is less combustible and
       incinerate.
    - Observe all federal, state, and local laws concerning health and
       pollution.
                   SECTION VIII -- SAFE HANDLING AND USE INFORMATION
______
Respiratory Protection: - A NIOSH approved respirator for organic vapors
       should be worn if needed.
Ventilation: - Local exhaust recommended.
```

Page 2

Zeron Bikini Blue MSDS

- Mechanical (General) recommended.

- Special: None known.

Protective Gloves: - Should be worn. Eye Protection: - Safety glasses should be worn in any type of industrial

operation.

Other Protective Equipment: - Safety shower and eye bath in work area. Hygienic Practices: - Remove paint from skin contact after exposure.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing: - Material is classified as a flammable liquid. Keep away from heat, sparks and open flame. Keep container closed. Avoid eye contact, prolonged skin contact, and inhalation of high concentrations of vapor. Use with ventilation adequate to maintain vapor concentrations below the TLV of 50 PPM.

Other Precautions: - Hazardous product residue may remain after the product has been removed from its container. Do not reuse "empty" container without commercial cleaning or reconditioning. See also 29 code of federal regulation 1910.1000.