

Diving Board Resurface Kit MSDS Epoxy Catalyst Part Two
MATERIAL SAFETY DATA SHEET PAGE #1

FOR COATINGS, RESINS AND RELATED MATERIALS

DATE OF PREPARATION - 30, 03,2014

MANUFACTURER'S NAME : Kelley Technical Coatings
ADDRESS : 1445 South 15th Street
ADDRESS : PO Box 3726
ADDRESS :
CITY, STATE : Louisville, Kentucky, 40201-3726

EMERGENCY TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (800) 424-9300-
INFORMATION TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (502) 418-5086-

SECTION I -- PRODUCT IDENTIFICATION

MANUFACTURER'S CODE IDENTIFICATION :368C
PRODUCT CLASS : Epoxy Hardener
TRADE NAME : SUPER CONVOY CATALYST
HMIS INFORMATION : HEALTH : 02
FLAMMABILITY : 02
REACTIVITY : 01
PERSONAL PROTECTIVE EQUIPMENT : REFER TO "SECTION VIII"

SECTION II -- HAZARDOUS INGREDIENTS

INGREDIENT	Cas	%BY WEIGHT	ACGIH T.L.V.	OSHA P.E.L	SAR 313	NUIS PGMT
AROMATIC NAPHTHA	64742-95-6	55.534	100PPM	100PPM	Y	N

If indicated above; this material could constitute a personnel hazard.

If the CAS# field above starts with ## then this material is considered a trade secret.

SECTION III -- PHYSICAL DATA

LOWER EXPLOSION LEVEL 1.0 - 1.2
BOILING RANGE HIGH 335 DF LOW 306 DF
VAPOR PRESSURE 3.00 MMHG @ 68DF
VAPOR DENSITY HEAVIER THAN AIR
EVAPORATION RATE SLOWER THAN BUTYL ACETATE
WEIGHT PER GALLON 7.58
% VOLATILE BY VOLUME 58.71
% VOLATILE BY WEIGHT 55.53
VOC --- LBS/GAL 4.28 LBS/GAL No Water 4.28

MATERIAL SAFETY DATA SHEET

PAGE #2

MANUFACTURER'S CODE 368C DATE OF PREPARATION - 30, 03,2014
TRADE NAME SUPER CONVOY CATALYST,
GRAMS/LITER 513.6 GRAMS/LITER 513.6

SECTION IV -- FIRE AND EXPLOSION DATA

FLAMMABILITY CLASSIFICATION OSHA - CLASS II
DOT - COMBUSTIBLE LIQUID UN 1263
LOWEST FLASH POINT T.C.C. 110 DF
LOWER EXPLOSION LEVEL (LEL) 1%

Diving Board Resurface Kit MSDS Epoxy Catalyst Part Two
Extinguishing Media: (Yes) - Foam (No) - Alcohol Foam (Yes) - CO2
(Yes) - Dry Chemical (Yes) - Water Fog
Unusual Fire and Explosion Hazards: - Flammable vapors may form explosive mixtures with air.
Special Fire Fighting Procedures: - Avoid solid stream of water, use fog for cooling.

SECTION V -- HEALTH HAZARD DATA

To the best of our knowledge, this product does not contain any carcinogenic ingredients.
Effects of Overexposure: - Liquid may cause eye burns. Prolonged skin contact with liquid may cause irritation. Eye, nose and throat irritation may result from exposure to vapor. Narcotic effects occur at higher concentrations of vapor.
Primary Route(s) of Entry: (X) - Dermal (X) - Inhalation (X) - Ingestion
Emergency and First Aid Procedures:
- Eye contact: Irrigate immediately and thoroughly with water at least 15 minutes and get medical attention.
- Skin contact: Flush immediately and thoroughly with water.
- Inhalation: Remove from exposure, treat symptomatically and get medical attention.
Medical Conditions Prone to Aggravation by Exposure:
- Pre-existing Respiratory, Eye and Skin Conditions.

SECTION VI -- REACTIVITY DATA

Stability: () - Unstable (X) - Stable
Hazardous Polymerization: () - May Occur (X) - will Not Occur
Hazardous Decomposition Products: - As with any other organic material, combustion will produce carbon dioxide and probably carbon monoxide.
Conditions to Avoid: - Not applicable.
Incompatibility (Materials to Avoid): - Oxidizing materials can cause a vigorous reaction.

MATERIAL SAFETY DATA SHEET

PAGE #3

MANUFACTURER'S CODE 368C DATE OF PREPARATION - 30,03,2014
TRADE NAME SUPER CONVOY CATALYST,

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Leaked or Spilled:
- Eliminate all ignition sources. Flush spill away with water spray.
- Small spills may be collected with absorbant material.
Waste Disposal Method:
- Mix with a compatible chemical which is less combustibile and incinerate.
- Observe all federal, state, and local laws concerning health and pollution.

SECTION VIII -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: - A NIOSH approved respirator for organic vapors should be worn if needed.
Ventilation: - Local exhaust recommended.
- Mechanical (General) recommended.
- Special: None known.
Protective Gloves: - Should be worn.
Eye Protection: - Safety glasses should be worn in any type of industrial operation.

Diving Board Resurface Kit MSDS Epoxy Catalyst Part Two
Other Protective Equipment: - Safety shower and eye bath in work area.
Hygienic Practices: - Remove paint from skin contact after exposure.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing: -
Keep away from heat, sparks and open flame.
Keep container closed. Avoid eye contact, prolonged skin contact, and
inhalation of high concentrations of vapor. Use with ventilation
adequate to maintain vapor concentrations below the TLV of 50 PPM.
Other Precautions: - Hazardous product residue may remain after the
product has been removed from its container. Do not reuse "empty"
container without commercial cleaning or reconditioning. See also
29 code of federal regulation 1910.1000.

MATERIAL SAFETY DATA SHEET

PAGE #4

MANUFACTURER'S CODE 368C
TRADE NAME SUPER CONVOY CATALYST,

DATE OF PREPARATION - 30, 03,2014